



PINNACLE
DRYER
CORP.

Proudly Manufactured in the USA

MODEL #PDC-R10

General Specifications for the PDC-R10

THE BRAND AND MODEL NUMBER SHOWN ARE TO ESTABLISH THE LEVEL OF QUALITY EXPECTED FOR THE REQUIREMENT. THE PDC-R10 RECESSED HAND DRYER AS MANUFACTURED BY PINNACLE DRYER CORPORATION WILL BE THE BENCHMARK. OTHER BRANDS WILL BE CONSIDERED IF THEY MEET THE FUNCTIONALITY, OPERATION AND RUGGEDNESS REQUIRED.

The dryer shall be touchless and activated by an infra-red light. The machine shall run only for the time that the user's hands are inside the drying chamber. No button shall be required. Hands shall fit into recessed cavity where the warm air is recycled, allowing for a quick and energy efficient drying time of 20-25 seconds.

The dryer shall be ADA Compliant and shall enhance the environmental goals of sanitation and reduction of bacteria by not requiring the user to touch any controls.

Overheat protection should be provided by state-of-the-art circuitry, featuring an automatic cut-off which activates after 60 seconds of continuous use. The dryer shall automatically reset itself after obstruction has been removed.

The dryer shall be totally recessed. The cover and drying chamber shall be made of 18 guage Stainless Steel. The cover shall be attached with four (4) 1/4"-20 x 1/2" Torx screws with Vandal Resistant pin. Standard electrical knock-out shall be located on the top and bottom of the recessed box. The dryer shall be capable of mounting in either a 6" block wall, an 8" block wall or a 4" stud wall. Mounting brackets are provided that allow unit to be attached to finished outside wall surface. The machine shall draw 11.5 Amps @ 120 Vac Nominal.

THE PDC-R10 IS A UNIQUE, STATE-OF-THE-ART HAND DRYER. MADE IN THE USA. PLEASE CALL 800-943-7937 FOR A QUOTATION.

307 Fields Drive
Aberdeen, NC 28315
Phone (800) 943-7937 ♦ (910) 944-2117 ♦ Fax (910) 944-9430
www.pinnacledryer.com