



PINNACLE
DRYER
CORP.

Proudly Manufactured in the USA

MODEL #P3-12S

General Specifications for the P3-12S

THE BRAND AND MODEL NUMBER SHOWN ARE TO ESTABLISH THE LEVEL OF QUALITY EXPECTED FOR THIS REQUIREMENT. THE P3-12S SURFACE MOUNT HAND DRYER AS MANUFACTURED BY PINNACLE DRYER CORPORATION WILL BE THE BENCHMARK. OTHER BRANDS WILL BE CONSIDERED IF THEY MEET THE FUNCTIONALITY, OPERATION AND RUGGEDNESS REQUIRED.

The dryer shall be touchless and activated by an infra-red light. The machine shall run only for the time that the user's hands are inside the drying chamber. No button shall be required. Hands shall fit into recessed cavity where the warm air is recycled, allowing for a quick and energy efficient drying time of 20-25 seconds.

The dryer shall be ADA Compliant and shall enhance the environmental goals of sanitation and reduction of bacteria by not requiring the user to touch any controls.

Overheat protection should be provided by state-of-the-art circuitry, featuring an automatic cut-off which activates after 60 seconds of continuous use. The dryer shall automatically reset itself after obstruction has been removed.

The dryer shall be surface mounted. The cover shall be made of 20 gauge Stainless Steel. The cover shall be attached with 1/4"-20 x 1/2" Torx Button screws with Vandal Resistant pin. Standard electrical knock-out shall be located on the back mounting plate of the dryer. Optional knock-outs shall be provided on the top and bottom of the cover. The dryer shall be capable of mounting on any surface wall. The machine shall draw 11 Amps @ 120 Vac Nominal.

THE P3-12S IS A UNIQUE, STATE-OF-THE-ART HAND DRYER. MADE IN THE USA. PLEASE CALL 800-943-7937 FOR A QUOTATION.

307 Fields Drive
Aberdeen, NC 28315
Phone (800) 943-7937 ♦ (910) 944-2117 ♦ Fax (910) 944-9430
www.pinnacledryer.com